

[72] Inventor **Paul Wuthrich**
Woodbury, Conn.
 [21] Appl. No. **820,189**
 [22] Filed **Apr. 29, 1969**
 [45] Patented **Aug. 3, 1971**
 [73] Assignee **Timex Corporation**
Waterbury, Conn.

[56]

References Cited

UNITED STATES PATENTS

| | | | |
|-----------|---------|-------------------|---------|
| 371,696 | 10/1887 | Meads..... | 58/19 |
| 1,037,130 | 8/1912 | Christianson..... | 58/19 |
| 1,383,560 | 7/1921 | Osieck..... | 58/19 |
| 1,521,600 | 1/1925 | Crowe..... | 58/19 |
| 1,529,852 | 3/1925 | Tanglin..... | 58/57.5 |

Primary Examiner—Richard B. Wilkinson

Assistant Examiner—Lawrence R. Franklin

Attorney—Richard A. Joel

[54] ALARM DEVICE FOR A HOROLOGICAL INSTRUMENT

5 Claims, 4 Drawing Figs.

[52] U.S. Cl..... 58/19,
 58/57.5
 [51] Int. Cl..... G04c 21/20
 [50] Field of Search..... 58/19, 19
 A, 19 B, 57.5

ABSTRACT: A horological instrument includes a source of electrical energy and an electrical audible alarm. The circuit between the energy source and the alarm is normally open. A setting stem rotates a geared disc. The disc carries a conductive track and a conductive contact point. The contact point, normally twice a day, contacts a portion of the hour wheel, closing the circuit and allowing the alarm to sound.

